

Supply Power for up to



3475, 3475-80 or 3500 Blast Lights

Product Features

Input:	90 to 264 volts, 47 to 63Hz, 2.2 amps maximum
Output:	24 volts DC, 4.2 amps maximum
Input AC/Cord:	-4KS model: 5.5 ft (1.7 meters) 14/3 SOOW, -4KSX100 model: 100' (30 meters) 16/3 SOOW
Output Cords:	Output cord lengths are 14 to 16 inches (36 to 41cm) Western Technology Extreme Cable, AWG 16/2 -4KS model: Four 3115-1 receptacles -4KSX100 model: Turck-type female 5-pin, with pin 3 minus, pin 4 plus
Controls:	One, Kill Switch, Pull ON, Push OFF
Enclosure: —Dimensions	Unfinished cast aluminum 8 5/8" (220mm) X 5 3/4" (145mm) X 3 1/4" (83mm)
Weight:	-4KS – 5.5lbs (2.5kg), -4KSX100 – 14.8lbs (6.7kg)
Temperature:	Operating Temperature – minus 25°C to 60°C Storage Temperature – minus 40°C to 80°C
Vibration:	10 to 500Hz 2g

Environmental Certifications

Enclosure Seal:	IP68, NEMA 4, 4X, 12, 13
Electrical Certifications of Internal Power Supply:	EMI – EMC Emissions Compliance to BS N/EN55032 (CISPR32) Class B, BS EN/EN61000-3-2 Class A (80% load), BS EN/EN61000-3-3, EAC TP TC 020 EMC Immunity Compliance to BS EN/EN61000-4-2, 3, 4, 5, 6, 8, 11; BS EN/EN55035, light industry level, EAC TP TC 020 Safety Standards - UL8750, CSA C22.2 No 250.13-12, UL879, CSA C22.2 No.207-M89, BIS IS15885 (Note12), EAC TP TC 004, IEC62368-1, BS EN/EN62368-1 approved

Pictured:
3500/3475 LEDPP-4KS
Four-Out Power Supply & Plug



Model 3475/3500LEDPP-4KS

POWER SUPPLY – 4 Out, 6' 14/3 SOOW
with kill switch and female mini twist lock plug
3115-1

Model 3475/3500LEDPP-4KSX100

POWER SUPPLY – 4 Out, 100' 16/3 SOOW
with kill switch and turck plugs

